

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claim 1 (Currently amended): A developer fuser comprising:

a first heating element for transferring energy

a second heating element for transferring energy

a controller, controlling a first value of a first parameter of ~~at least one of power to, current through, frequency to, resonance of, inductance of, voltage across, and temperature at the~~ first heating element and a second value of the first parameter of the second heating element, for fusing a developer to a media

wherein the first value ~~at least one of power to, current through, frequency to, resonance of, inductance of, voltage across, and temperature at the first heating element~~ is different in magnitude from the second value, ~~at least one of power to, current through, frequency to, resonance of, inductance of, voltage across, and temperature at the second heating element.~~

Claim 2 (Currently amended): The developer fuser of claim 1,

wherein the controller is further controlling the first value ~~at least one of power to, current through, frequency to, resonance of, inductance of, voltage across, and temperature at the first heating element~~ based on a first datum from a first sensor ~~at least one of a first temperature sensor associated with the first heating element, a humidity sensor, a media thickness sensor, a media moisture content sensor, a media temperature sensor, and a developer temperature sensor~~

and is further controlling the second value ~~at least one of power to, current through, frequency to, resonance of, inductance of, voltage across, and temperature at the second heating element~~ based on a second datum from a second sensor, ~~at least one of a second temperature sensor associated with the second heating element, the humidity sensor, the media thickness sensor, the media moisture content sensor, the media temperature sensor, and the developer temperature sensor.~~

Claim 3 (Original): An image forming apparatus comprising the developer fuser of claim 1.

Claim 4 (Original): A copy machine comprising the developer fuser of claim 1.

Claim 5 (Currently amended): A controller for a developer fuser adapted to:

receive a media type datum, a first temperature sensor datum, and a second temperature sensor datum,

control a first value of a variable parameter of ~~at least one of power to, current through, frequency to, resonance of, inductance of, voltage across, and temperature at~~ a first heating element and a second value of the variable parameter of a second heating element based on the media type datum, the first temperature sensor datum, and the second temperature sensor datum,

wherein the first value ~~at least one of power to, current through, frequency to, resonance of, inductance of, voltage across, and temperature at the first heating element~~ is different in magnitude from the second value, ~~at least one of power to, current through, frequency to, resonance of, inductance of, voltage across, and temperature at the second heating element.~~

Claim 6 (Currently amended): The controller for a developer fuser of claim 5, wherein the controller is further adapted to

receive at least one of a humidity datum, a media thickness datum, a media moisture content datum, a media temperature datum, and a developer temperature datum, and

control the first value and the second value ~~at least one of power to, current through, frequency to, resonance of, inductance of, voltage across, and temperature at the first heating element and the second heating element~~ based on at least one of the humidity datum, the media thickness datum, the media moisture content datum, the media temperature datum, and the developer temperature datum.

Claim 7 (Original): An image forming apparatus comprising the controller for the developer fuser of claim 5.

Claim 8 (Original): A copy machine comprising the controller for the developer fuser of claim 5.

Claim 9 (Currently amended): A system for fusing developer comprising:

a first resonance circuit comprising a switching element, a power source and a first coil,
a second resonance circuit comprising the switching element, the power source and a second coil, the second coil electrically connected to the first coil at a node,

wherein the switching element is adapted to cause a first reduced frequency through the first resonance circuit, the first reduced frequency depending on a media type and a datum of a first ~~temperature~~ sensor associated with the first coil, and a second reduced frequency through the second resonance circuit, the second reduced frequency depending on the media type and a datum of a second ~~temperature~~ sensor associated with the second coil.

Claim 10 (Currently amended): The system for fusing developer of claim 9 18, wherein
the first reduced frequency further depends on a datum from at least one of a the first
temperature sensor associated with the first coil, a humidity sensor, a media thickness sensor, a
media moisture content sensor, a media temperature sensor, and a developer temperature sensor,
and

the second reduced frequency further depends on a datum from at least one of a second
temperature sensor associated with the second coil, the humidity sensor, the media thickness
sensor, the media moisture content sensor, the media temperature sensor, and the developer
temperature sensor.

Claim 11 (Original): An image forming apparatus comprising the system for fusing developer of
claim 9.

Claim 12 (Original): A copy machine comprising the system for fusing developer of claim 9.

Claim 13 (Currently amended): A process for reducing power consumption in a developer fuser
comprising:

a control system controlling a first value of a first parameter of at least one of power to,
~~current through, frequency to, resonance of, inductance of, voltage across, and temperature at~~ a
first heating element and a second value of the first parameter of a second heating element to
maintain a standby temperature,

the control system receiving a signal to fuse developer,

the control system controlling the first value and the second value at least one of power
~~to, current through, frequency to, resonance of, inductance of, voltage across, and temperature at~~

~~the first heating element and the second heating element based on at least one of a media type datum, a datum of a first temperature sensor associated with the first heating element, and a datum of a second temperature sensor associated with the second heating element, to fuse the developer,~~

~~the control system receiving a signal to return to maintain the standby temperature,~~

~~the control system controlling the first value and the second value at least one of power to, current through, frequency to, resonance of, inductance of, voltage across, and temperature at the first heating element and the second heating element to maintain the standby temperature.~~

Claim 14 (Currently amended): The process for reducing power consumption in a developer fuser of claim 13, wherein the control system controlling step to fuse the developer further comprises the control system controlling the first value and the second value at least one of power to, current through, frequency to, resonance of, inductance of, voltage across, and temperature at the first heating element and the second heating element based on a datum from a sensor selected from the group consisting of at least one of a first temperature sensor associated with the first heating element, a second temperature sensor associated with the second heating element, a humidity sensor, a media thickness sensor, a media moisture content sensor, a media temperature sensor, and a developer temperature sensor.

Claim 15 (New): The developer fuser of claim 1

wherein the first parameter is selected from the group consisting of power to, current through, frequency to, resonance of, inductance of, voltage across, and temperature at the respective heating element.

Claim 16 (New): The developer fuser of claim 15 wherein

the controller further controlling a third value of a second parameter of the first heating element and a fourth value of the second parameter of the second heating element, for fusing the developer to the media

wherein the second parameter is different from the first parameter and is selected from the group consisting of power to, current through, frequency to, resonance of, inductance of, voltage across, and temperature at the respective heating element.

Claim 17 (New): The developer fuser of claim 2

wherein the first sensor and the second sensor are of the same kind and are selected from the group consisting of a temperature sensor associated with the respective heating element, a humidity sensor, a media thickness sensor, a media moisture content sensor, a media temperature sensor, and a developer temperature sensor.

Claim 18 (New): The system for fusing developer of claim 9

wherein the first sensor and the second sensor comprise temperature sensors.

Claim 19 (New): The process for reducing power consumption in a developer fuser of claim 13

wherein the first parameter is selected from the group consisting of power to, current through, frequency to, resonance of, inductance of, voltage across, and temperature at the respective heating element.

Claim 20 (New): The process for reducing power consumption in a developer fuser of claim 19 wherein

controlling a third value of a second parameter of the first heating element and a fourth value of the second parameter of the second heating element to fuse the developer

wherein the second parameter is different from the first parameter and is selected from the group consisting of power to, current through, frequency to, resonance of, inductance of, voltage across, and temperature at the respective heating element.